



SAFETY DATA SHEET

DDP SPECIALTY ELECTRONIC MATERIALS US 9, LLC

Product name: MOLYKOTE® D-6818 Anti-Friction Coating

Issue Date: 05/06/2024

Print Date: 05/08/2024

DDP SPECIALTY ELECTRONIC MATERIALS US 9, LLC encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: MOLYKOTE® D-6818 Anti-Friction Coating

Recommended use of the chemical and restrictions on use

Identified uses: Lubricants and lubricant additives

COMPANY IDENTIFICATION

DDP SPECIALTY ELECTRONIC MATERIALS
US 9, LLC
974 Centre Road
Wilmington DE 19805
UNITED STATES

Customer Information Number:

833-338-7668

SDSQuestion-NA@dupont.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 1-800-424-9300

Local Emergency Contact: 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids - Category 3

Serious eye damage - Category 1

Reproductive toxicity - Category 1B

Specific target organ toxicity - repeated exposure - Category 2 - Inhalation

Label elements

Hazard pictograms



Signal word: **DANGER!**

Hazards

Flammable liquid and vapour.
Causes serious eye damage.
May damage fertility or the unborn child.
May cause damage to organs (Auditory system) through prolonged or repeated exposure if inhaled.

Precautionary statements

Prevention

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe mist or vapours.
Do not breathe spray.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
IF exposed or concerned: Get medical advice/ attention.
In case of fire: Avoid breathing fume.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage

Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

No data available

Further information

The values listed below represent the percentages of ingredients of unknown toxicity.
The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity: 1.05 %

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Inorganic and organic compounds, Mixture
This product is a mixture.

Component	CASRN	Concentration
------------------	--------------	----------------------

N-Ethyl-2-pyrrolidone	2687-91-4	>= 40.0 - < 50.0 %
Aluminum oxide	1344-28-1	>= 10.0 - < 20.0 %
Xylene	1330-20-7	>= 5.0 - < 10.0 %
Ethylbenzene	100-41-4	>= 5.0 - < 10.0 %
Molybdenum disulfide	1317-33-5	>= 5.0 - < 10.0 %
Graphite	7782-42-5	>= 1.0 - < 5.0 %

4. FIRST AID MEASURES

Description of first aid measures

General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: No emergency medical treatment necessary.

Skin contact: Wash off with plenty of water. Suitable emergency safety shower facility should be available in work area.

Eye contact: Wash immediately and continuously with flowing water for at least 30 minutes. Remove contact lenses after the first 5 minutes and continue washing. Obtain prompt medical consultation, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available. Get medical attention immediately.

Ingestion: No emergency medical treatment necessary.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Water spray Alcohol-resistant foam Carbon dioxide (CO₂) Dry chemical

Unsuitable extinguishing media: High volume water jet Do not use direct water stream.

Special hazards arising from the substance or mixture

Hazardous combustion products: Carbon oxides Nitrogen oxides (NOx) Sulphur oxides Fluorine compounds

Unusual Fire and Explosion Hazards: Flash back possible over considerable distance. Exposure to combustion products may be a hazard to health. Toxic vapours are evolved. Vapours may form explosive mixtures with air.

Advice for firefighters

Fire Fighting Procedures: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Do not use a solid water stream as it may scatter and spread fire.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Wear neoprene gloves to prevent contact with hydrofluoric acid.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions: Do not release the product to the aquatic environment above defined regulatory levels. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapours/mists with a water spray jet. Clean up remaining materials from spill with suitable absorbant. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

See sections: 7, 8, 11, 12 and 13.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not get on skin or clothing. Do not breathe vapours or spray mist. Do not swallow. Do not get in eyes. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste

and minimize release to the environment. Non-sparking tools should be used. Handle in accordance with good industrial hygiene and safety practice.

Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation. Ground and bond container and receiving equipment.

Conditions for safe storage: Keep in properly labelled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.

Do not store with the following product types: Strong oxidizing agents. Organic peroxides. Flammable solids. Pyrophoric liquids. Pyrophoric solids. Self-heating substances and mixtures. Substances and mixtures, which in contact with water, emit flammable gases. Explosives. Gases. Unsuitable materials for containers: None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
Aluminum oxide	OSHA Z-1	TWA total dust	15 mg/m3
	OSHA Z-1	TWA respirable fraction	5 mg/m3
	ACGIH	TWA Respirable particulate matter	1 mg/m3 , Aluminium
	Further information: A4: Not classifiable as a human carcinogen		
	CAL PEL	PEL Total dust	10 mg/m3
	CAL PEL	PEL respirable dust fraction	5 mg/m3
	Further information: (n): The concentration and percentage of the particulate used for this limit are determined from the fraction passing a size selector with the following characteristics: Aerodynamic Diameter in Micrometers (unit density sphere)..... Percent Passing Selector 0 100 1 97 2 91 3 74 4 50 5 30 6 17 7 9 8 5 10 1		
	OSHA P0	TWA Total dust	10 mg/m3
	OSHA P0	TWA respirable dust fraction	5 mg/m3
Xylene	DUPONT AEL	AEL *	100 ppm
	OSHA Z-1	TWA	435 mg/m3 100 ppm
	ACGIH	TWA	20 ppm
	Further information: OTO: Ototoxicant; A4: Not classifiable as a human carcinogen		
	CAL PEL	STEL	655 mg/m3 150 ppm
	CAL PEL	C	300 ppm
	CAL PEL	PEL	435 mg/m3 100 ppm
Ethylbenzene	DUPONT AEL	AEL *	20 ppm
	ACGIH	TWA	20 ppm
	Further information: OTO: Ototoxicant; A3: Confirmed animal carcinogen with unknown relevance to humans		

	OSHA Z-1	TWA	435 mg/m3 100 ppm
	CAL PEL	PEL	22 mg/m3 5 ppm
	CAL PEL	STEL	130 mg/m3 30 ppm
	NIOSH REL	TWA	435 mg/m3 100 ppm
	NIOSH REL	ST	545 mg/m3 125 ppm
Molybdenum disulfide	OSHA Z-1	TWA total dust	15 mg/m3 , Molybdenum
	ACGIH	TWA Inhalable particulate matter	10 mg/m3 , Molybdenum
	ACGIH	TWA Respirable particulate matter	3 mg/m3 , Molybdenum
	CAL PEL	PEL Total dust	10 mg/m3 , Molybdenum
	CAL PEL	PEL respirable dust fraction	3 mg/m3 , Molybdenum
	Further information: (n): The concentration and percentage of the particulate used for this limit are determined from the fraction passing a size selector with the following characteristics: Aerodynamic Diameter in Micrometers (unit density sphere)..... Percent Passing Selector 0 100 1 97 2 91 3 74 4 50 5 30 6 17 7 9 8 5 10 1		
Graphite	OSHA Z-3	TWA Dust	15 Million particles per cubic foot
	OSHA Z-1	TWA total dust	15 mg/m3
	OSHA Z-1	TWA respirable fraction	5 mg/m3
	ACGIH	TWA Respirable particulate matter	2 mg/m3
	CAL PEL	PEL Total dust	10 mg/m3
	CAL PEL	PEL respirable dust fraction	5 mg/m3
	Further information: (n): The concentration and percentage of the particulate used for this limit are determined from the fraction passing a size selector with the following characteristics: Aerodynamic Diameter in Micrometers (unit density sphere)..... Percent Passing Selector 0 100 1 97 2 91 3 74 4 50 5 30 6 17 7 9 8 5 10 1		
	CAL PEL	PEL Respirable dust	2.5 mg/m3
	NIOSH REL	TWA Respirable	2.5 mg/m3
	OSHA P0	TWA Total dust	10 mg/m3
	OSHA P0	TWA respirable dust fraction	5 mg/m3
	OSHA P0	TWA respirable dust fraction	2.5 mg/m3

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Xylene	1330-20-7	Methylhippu	Urine	End of	1.5 g/g	ACGIH

		ric acids		shift (As soon as possible after exposure ceases)	creatinine	BEI
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI

Exposure controls

Engineering measures: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations.

Individual protection measures

Eye/face protection: Use chemical goggles.

Skin protection

Hand protection: Use gloves chemically resistant to this material. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. If there are no applicable exposure limit requirements or guidelines, use an approved respirator.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	liquid
Color	black
Odor	Solvent odor
Odor Threshold	No data available
pH	No data available
Melting point/range	No data available
Freezing point	No data available
Boiling point (760 mmHg)	> 35 °C (> 95 °F)
Flash point	closed cup 44 °C (111 °F)

Evaporation Rate (Butyl Acetate = 1)	No data available
Flammability (solid, gas)	Not Applicable
Lower explosion limit	No data available
Upper explosion limit	No data available
Vapor Pressure	No data available
Relative Vapor Density (air = 1)	No data available
Relative Density (water = 1)	1.2
Water solubility	No data available
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Dynamic Viscosity	340 mPa.s at 25 °C (77 °F)
Kinematic Viscosity	No data available
Explosive properties	Not explosive
Oxidizing properties	The substance or mixture is not classified as oxidizing.
Molecular weight	No data available
Particle size	Not applicable

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Can react with strong oxidizing agents. When heated to temperatures above 150 °C (300 °F) in the presence of air, product can form formaldehyde vapours. Safe handling conditions may be maintained by keeping vapour concentrations within the occupational exposure limit for formaldehyde. Vapours may form explosive mixture with air. Flammable liquid and vapour.

Conditions to avoid: Heat, flames and sparks.

Incompatible materials: Oxidizing agents

Hazardous decomposition products: Hydrogen Fluoride. Carbonic difluoride. Carbon monoxide. 1,1,1,3,3,3-Hexafluoro-2-propanone. Hexafluoroethane.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity

Product test data not available. Refer to component data.

Acute dermal toxicity

Product test data not available. Refer to component data.

Acute inhalation toxicity

Product test data not available. Refer to component data.

Skin corrosion/irritation

Product test data not available. Refer to component data.

Serious eye damage/eye irritation

Product test data not available. Refer to component data.

Sensitization

Product test data not available. Refer to component data.

Specific Target Organ Systemic Toxicity (Single Exposure)

Product test data not available. Refer to component data.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Product test data not available. Refer to component data.

Carcinogenicity

Product test data not available. Refer to component data.

Teratogenicity

Product test data not available. Refer to component data.

Reproductive toxicity

Product test data not available. Refer to component data.

Mutagenicity

Product test data not available. Refer to component data.

Aspiration Hazard

Product test data not available. Refer to component data.

COMPONENTS INFLUENCING TOXICOLOGY:

N-Ethyl-2-pyrrolidone

Acute oral toxicity

LD50, Rat, male and female, 3,200 mg/kg

Acute dermal toxicity

LD50, Rat, male and female, > 2,000 mg/kg No deaths occurred at this concentration.

Acute inhalation toxicity

LC50, Rat, male and female, 4 Hour, dust/mist, > 5.1 mg/l No deaths occurred at this concentration.

Skin corrosion/irritation

Brief contact may cause slight skin irritation with local redness.

Serious eye damage/eye irritation

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

Sensitization

Did not demonstrate the potential for contact allergy in mice.

For respiratory sensitization:
No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

In animals, effects have been reported on the following organs:
Liver.

Carcinogenicity

No relevant data found.

Teratogenicity

Has caused birth defects in laboratory animals. Has been toxic to the fetus in laboratory animal tests.

Reproductive toxicity

In animal studies, it has been shown to cause effects on sperm which may interfere with fertility in males.

Mutagenicity

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Aspiration Hazard

Aspiration into the lungs may occur during ingestion or vomiting, causing lung damage or even death due to chemical pneumonia.

Aluminum oxide

Acute oral toxicity

LD50, Rat, > 5,000 mg/kg OECD Test Guideline 401

Acute dermal toxicity

The dermal LD50 has not been determined.

Acute inhalation toxicity

LC50, Rat, male and female, dust/mist, > 2.3 mg/l No deaths occurred at this concentration.

Skin corrosion/irritation

Brief contact is essentially nonirritating to skin.
Mechanical injury only.

Serious eye damage/eye irritation

Solid or dust may cause irritation or corneal injury due to mechanical action.

Sensitization

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Repeated excessive exposures to alumina (aluminium oxide) dust or fumes may cause respiratory effects.

Exposure to alumina alone has not been shown to cause chronic lung disease. Some forms of alumina, when injected directly into the lungs of animals, caused fibrosis, but this is an abnormal route of exposure.

Carcinogenicity

Although certain forms of alumina have been reported to induce tumors when injected directly into the lungs of laboratory animals, there is no evidence that alumina is carcinogenic under normal routes of exposure.

Teratogenicity

High doses of aluminium and aluminium salts given to laboratory animals during pregnancy have caused developmental toxicity in the fetus at doses mildly toxic to the mother. The relevance of these data to alumina is unknown.

Reproductive toxicity

No relevant data found.

Mutagenicity

For similar material(s): In vitro genetic toxicity studies were negative in some cases and positive in other cases. Animal genetic toxicity studies were negative in some cases and positive in other cases.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

Xylene

Acute oral toxicity

LD50, Rat, 3,523 mg/kg

Acute dermal toxicity

LD50, Rabbit, > 4,200 mg/kg

Acute inhalation toxicity

LC50, Rat, 4 Hour, vapour, 27.5 mg/l

Skin corrosion/irritation

Prolonged contact may cause skin irritation with local redness.

Repeated contact may cause skin burns. Symptoms may include pain, severe local redness, swelling, and tissue damage.

Vapor may cause skin irritation.

May cause drying and flaking of the skin.

Serious eye damage/eye irritation

May cause moderate eye irritation.

May cause slight temporary corneal injury.

Vapor may cause eye irritation experienced as mild discomfort and redness.

Sensitization

Did not demonstrate the potential for contact allergy in mice.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

May cause respiratory irritation.

May cause drowsiness or dizziness.

Route of Exposure: Inhalation

Target Organs: Respiratory system, Central nervous system

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Xylene is reported to have caused hearing loss in laboratory animals upon exposure to high concentrations; such effects have not been reported in humans.

Carcinogenicity

Xylene was not found to be carcinogenic in a National Toxicology Program bioassay in rats and mice.

Teratogenicity

Exaggerated doses of xylene given orally to pregnant mice resulted in an increase in cleft palate, a common developmental abnormality in mice. In animal inhalation studies, xylene caused toxicity to the fetus but did not cause birth defects. Available data are inadequate for evaluation of maternal toxicity.

Reproductive toxicity

In animal studies, did not interfere with reproduction.

Mutagenicity

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Aspiration Hazard

May be fatal if swallowed and enters airways.

Ethylbenzene

Acute oral toxicity

LD50, Rat, 3,500 mg/kg

Acute dermal toxicity

LD50, Rabbit, 15,500 mg/kg

Acute inhalation toxicity

LC50, Rat, 4 Hour, vapour, 17.2 mg/l

Skin corrosion/irritation

Brief contact may cause moderate skin irritation with local redness. Prolonged contact may cause skin burns. Symptoms may include pain, severe local redness, swelling, and tissue damage. May cause drying and flaking of the skin.

Serious eye damage/eye irritation

May cause moderate eye irritation. Vapor may cause lacrimation (tears).

Sensitization

For skin sensitization:
Did not cause allergic skin reactions when tested in humans.

For respiratory sensitization:
No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

In animals, effects have been reported on the following organs:
May cause hearing loss based on animal data.
Kidney.
Liver.
Lung.
Although one early inhalation study on ethylbenzene reported an adverse effect on the testes, recent, more comprehensive studies have not shown this effect.

Carcinogenicity

Ethylbenzene has been shown to cause cancer in laboratory animals. There is no evidence that these findings are relevant to humans.

Teratogenicity

Has caused birth defects in laboratory animals only at doses toxic to the mother. Has been toxic to the fetus in lab animals at doses nontoxic to the mother.

Reproductive toxicity

In animal studies, did not interfere with reproduction. In animal studies, did not interfere with fertility.

Mutagenicity

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Aspiration Hazard

Aspiration into the lungs may occur during ingestion or vomiting, causing lung damage or even death due to chemical pneumonia. May be fatal if swallowed and enters airways.

Molybdenum disulfide

Acute oral toxicity

LD50, Rat, > 2,000 mg/kg No deaths occurred at this concentration.

Acute dermal toxicity

LD50, Rat, male and female, > 2,000 mg/kg No deaths occurred at this concentration.

Acute inhalation toxicity

LC50, Rat, 4 Hour, dust/mist, > 2.82 mg/l No deaths occurred at this concentration.

Skin corrosion/irritation

Brief contact is essentially nonirritating to skin.

Prolonged contact may cause slight skin irritation with local redness.

Serious eye damage/eye irritation

May cause slight temporary eye irritation.

Corneal injury is unlikely.

Sensitization

For skin sensitization:

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

No relevant data found.

Carcinogenicity

No relevant data found.

Teratogenicity

No relevant data found.

Reproductive toxicity

No relevant data found.

Mutagenicity

For similar material(s): In vitro genetic toxicity studies were negative.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

Graphite

Acute oral toxicity

LD50, Rat, > 2,000 mg/kg OECD Test Guideline 423

Acute dermal toxicity

The dermal LD50 has not been determined.

Acute inhalation toxicity

An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration. LC50, Rat, 4 Hour, dust/mist, > 2 mg/l OECD Test Guideline 403

Skin corrosion/irritation

Brief contact is essentially nonirritating to skin.

Serious eye damage/eye irritation

May cause slight temporary eye irritation.

Sensitization

Did not demonstrate the potential for contact allergy in mice.

Specific Target Organ Systemic Toxicity (Single Exposure)

The substance or mixture is not classified as specific target organ toxicant, single exposure.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Teratogenicity

Did not cause birth defects or any other fetal effects in laboratory animals.

Reproductive toxicity

In animal studies, did not interfere with reproduction.

Mutagenicity

In vitro genetic toxicity studies were negative.

Aspiration Hazard

No aspiration toxicity classification

Carcinogenicity

Component

Ethylbenzene

List

IARC

ACGIH

Classification

Group 2B: Possibly carcinogenic to humans

A3: Confirmed animal carcinogen with unknown relevance to humans.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity

N-Ethyl-2-pyrrolidone

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

LC50, Zebra fish (Danio/Brachydanio rerio), static test, 96 Hour, 464 - 999 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, > 100 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

EC50, Desmodesmus subspicatus (green algae), static test, 72 Hour, Growth rate, > 100 mg/l, OECD Test Guideline 201

Toxicity to bacteria

EC50, Bacteria, 16 Hour, >1,000 mg/l

Chronic toxicity to aquatic invertebrates

Based on data from similar materials

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, 12.5 mg/l

Aluminum oxide

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

EC50, Fish, 96 Hour, > 100 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate inhibition, > 100 mg/l, OECD Test Guideline 201 or Equivalent

Chronic toxicity to fish

NOEC, Pimephales promelas (fathead minnow), 7 d, 7.1 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 28 d, 1.89 mg/l

Xylene

Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, 2.6 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, 3.82 mg/l

Acute toxicity to algae/aquatic plants

EC50, Selenastrum capricornutum (fresh water algae), 72 Hour, Growth rate, 4.9 mg/l, OECD Test Guideline 201 or Equivalent

NOEC, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate, 0.44 mg/l, OECD Test Guideline 201 or Equivalent

Chronic toxicity to fish

NOEC, Oncorhynchus mykiss (rainbow trout), flow-through, 56 d, mortality, > 1.3 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 21 d, 1.57 mg/l

Ethylbenzene

Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).
LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, 4.2 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), Static, 48 Hour, 1.8 - 2.4 mg/l

Acute toxicity to algae/aquatic plants

EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth inhibition (cell density reduction), 3.6 - 4.6 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

EC50, Bacteria, 16 Hour, > 12 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Ceriodaphnia dubia (water flea), semi-static test, 7 d, 0.96 mg/l

Toxicity to soil-dwelling organisms

LC50, Eisenia fetida (earthworms), 2 d, survival, 0.047 mg/cm²

Molybdenum disulfide

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

For similar material(s):

LC50, Fish, 96 Hour, > 100 mg/l

Acute toxicity to aquatic invertebrates

Based on data from similar materials

EC50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l

Acute toxicity to algae/aquatic plants

Based on data from similar materials

ErC50, algae, 72 Hour, Growth rate, > 100 mg/l

Toxicity to bacteria

EC50, 30 Hour, Respiration rates., > 100 mg/l

Chronic toxicity to fish

Based on data from similar materials

NOEC, Fish, 34 d, > 10 mg/l

Chronic toxicity to aquatic invertebrates

Based on data from similar materials

NOEC, Daphnia magna, 21 d, > 10 mg/l

Graphite

Acute toxicity to fish

No toxicity at the limit of solubility

LC50, Danio rerio (zebra fish), 96 Hour, > 100 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

No toxicity at the limit of solubility

EC50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

EC50, Raphidocelis subcapitata (freshwater green alga), 72 Hour, > 100 mg/l, OECD Test Guideline 201

NOEC, Raphidocelis subcapitata (freshwater green alga), 72 Hour, >= 100 mg/l, OECD Test Guideline 201

Toxicity to bacteria

EC50, 3 Hour, > 1,012.5 mg/l, OECD Test Guideline 209

Persistence and degradability**N-Ethyl-2-pyrrolidone**

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

Biodegradation: 90 - 100 %

Exposure time: 28 d

Method: OECD Test Guideline 301A

Aluminum oxide

Biodegradability: Biodegradability is not applicable to inorganic substances.

Xylene

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

Biodegradation: 87.8 %

Exposure time: 28 d

Method: OECD Test Guideline 301F or Equivalent

Theoretical Oxygen Demand: 3.17 mg/mg

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	37.000 %
10 d	58.000 %
20 d	72.000 %

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitization: OH radicals

Atmospheric half-life: 19.7 Hour

Method: Estimated.

Ethylbenzene

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

Biodegradation: 100 %
Exposure time: 6 d
Method: OECD Test Guideline 301E or Equivalent

Theoretical Oxygen Demand: 3.17 mg/mg Estimated.

Chemical Oxygen Demand: 2.62 mg/mg Dichromate

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	31.5 %
10 d	38.5 %
20 d	45.4 %

Photodegradation
Sensitization: OH radicals
Atmospheric half-life: 55 Hour
Method: Estimated.

Molybdenum disulfide

Biodegradability: Biodegradability is not applicable to inorganic substances.

Graphite

Biodegradability: Not applicable

Bioaccumulative potential

N-Ethyl-2-pyrrolidone

Bioaccumulation: Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected. Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): -0.2 at 20 °C Measured

Aluminum oxide

Bioaccumulation: Partitioning from water to n-octanol is not applicable.

Xylene

Bioaccumulation: Does not bioaccumulate.

Partition coefficient: n-octanol/water(log Pow): 3.16 at 20 °C

Bioconcentration factor (BCF): 25.9 Rainbow trout (Salmo gairdneri) Measured

Ethylbenzene

Partition coefficient: n-octanol/water(log Pow): 3.6 at 20 °C

Bioconcentration factor (BCF): 15 Fish Measured

Molybdenum disulfide

Bioaccumulation: Partitioning from water to n-octanol is not applicable.

Graphite

Bioaccumulation: Not applicable Not applicable

Mobility in soil**N-Ethyl-2-pyrrolidone**

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 14 Estimated.

Aluminum oxide

No relevant data found.

Xylene

Potential for mobility in soil is medium (Koc between 150 and 500).

Partition coefficient (Koc): 443 Estimated.

Ethylbenzene

Potential for mobility in soil is low (Koc between 500 and 2000).

Partition coefficient (Koc): 518 Estimated.

Molybdenum disulfide

No relevant data found.

Graphite

No relevant data found.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

14. TRANSPORT INFORMATION

DOT

Proper shipping name	Flammable liquids, n.o.s.(Ethylbenzene, Xylene)
UN number	UN 1993
Class	3

Packing group	III
Reportable Quantity	Xylene, Ethylbenzene

Classification for SEA transport (IMO-IMDG):

Proper shipping name	FLAMMABLE LIQUID, N.O.S.(Ethylbenzene, Xylene)
UN number	UN 1993
Class	3
Packing group	III
Marine pollutant	No
Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code	Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Proper shipping name	Flammable liquid, n.o.s.(Ethylbenzene, Xylene)
UN number	UN 1993
Class	3
Packing group	III

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Flammable (gases, aerosols, liquids, or solids)
 Serious eye damage or eye irritation
 Reproductive toxicity
 Specific target organ toxicity (single or repeated exposure)

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

The following components are subject to reporting levels established by SARA Title III, Section 313:

Components	CASRN
Aluminum oxide	1344-28-1
Xylene	1330-20-7
Ethylbenzene	100-41-4

California Prop. 65

WARNING: This product can expose you to chemicals including Ethylbenzene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the Active inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System

NFPA

Health	Flammability	Instability
3	2	0

HMIS

Health	Flammability	Physical Hazard
3*	2	0

* = Chronic Effects (See Hazards Identification)

Revision

Identification Number: 99117307 / A776 / Issue Date: 05/06/2024 / Version: 6.1

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	ACGIH - Biological Exposure Indices (BEI)
AEL *	12 hr. TWA
C	Ceiling
CAL PEL	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
DUPONT AEL	DuPont AEL (Acceptable Exposure Limit)
NIOSH REL	USA. NIOSH Recommended Exposure Limits
OSHA P0	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
PEL	Permissible exposure limit
ST	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
STEL	Short term exposure limit
TWA	8-hour time weighted average

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x%

growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DDP SPECIALTY ELECTRONIC MATERIALS US 9, LLC urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US